

Package: processpredictR (via r-universe)

August 22, 2024

Type Package

Title Process Prediction

Version 0.1.0

Date 2022-12-23

Description Means to predict process flow, such as process outcome, next activity, next time, remaining time, and remaining trace. Off-the-shelf predictive models based on the concept of Transformers are provided, as well as multiple ways to customize the models. This package is partly based on work described in Zaharah A. Bukhsh, Aaqib Saeed, & Remco M. Dijkman. (2021). ``ProcessTransformer: Predictive Business Process Monitoring with Transformer Network" <[arXiv:2104.00721](https://arxiv.org/abs/2104.00721)>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.3

Imports bupaR, edeaR, dplyr, forcats, magrittr, reticulate, tidyr, tidyselect, purrr, stringr, keras, tensorflow, rlang, data.table, mltools, ggplot2, cli, glue, plotly, progress

Config/testthat/edition 3

Depends R (>= 2.10)

Suggests knitr, rmarkdown, lubridate, eventdataR

VignetteBuilder knitr

NeedsCompilation no

Author Ivan Esin [aut], Gert Janssenswillen [cre], Hasselt University [cph]

Maintainer Gert Janssenswillen <gert.janssenswillen@uhasselt.be>

Date/Publication 2023-01-17 17:10:01 UTC

Repository <https://gertjanssenswillen.r-universe.dev>

RemoteUrl <https://github.com/cran/processpredictR>

RemoteRef HEAD

RemoteSha d7db44aab9aff3a2a75b1ae992899e75a30598c6

Contents

confusion_matrix	2
create_model	3
create_vocabulary	4
get_vocabulary	4
max_case_length	5
num_outputs	5
plot.ppred_predictions	6
ppred_examples_df	6
ppred_model	6
ppred_predictions	7
prepare_examples	7
print.ppred_model	8
processpredictR	8
split_train_test	9
stack_layers	9
tokenize	10
vocab_size	10
Index	12

confusion_matrix	<i>Confusion matrix for predictions</i>
------------------	---

Description

Confusion matrix for predictions

Usage

```
confusion_matrix(predictions, ...)
```

Arguments

predictions [ppred_predictions](#): A [data.frame](#) with predicted values returned by `predict.ppred_model()`.
 ... additional arguments.

Value

A [table](#) object that can be used for plotting a confusion matrix using `plot()`.

create_model	<i>Define transformer model</i>
--------------	---------------------------------

Description

Defines the model using the keras functional API. The following 4 process monitoring tasks are defined:

- outcome
- next_activity
- next_time
- remaining_time
- remaining_trace
- remaining_trace_s2s

Usage

```
create_model(  
  x_train,  
  custom = FALSE,  
  num_heads = 4,  
  output_dim_emb = 36,  
  dim_ff = 64,  
  ...  
)
```

Arguments

x_train	data.frame : A processed data.frame from prepare_examples() .
custom	logical (default <code>FALSE</code>): If <code>TRUE</code> , returns a custom model.
num_heads	A number of attention heads of the keras::layer_embedding() .
output_dim_emb	Dimension of the dense embedding of the keras::layer_embedding() .
dim_ff	Dimensionality of the output space of the feedforward network part of the model (units argument of the keras::layer_dense()).
...	you can pass additional arguments to keras::keras_model() (ex.: name argument).

Value

An object of class [ppred_model](#) and [list](#) containing a Transformer model (returned by [keras::keras_model\(\)](#)) and some additional useful metrics.

create_vocabulary *Create a vocabulary*

Description

Creates a vocabulary of activities and outcome labels.

Usage

```
create_vocabulary(processed_df)
```

Arguments

processed_df A preprocessed object of type `ppred_examples_df` returned by `prepare_examples()`.

Value

A `list` consisting of:

- "keys_x": `list` of activity labels
- "keys_y": `list` of outcome labels (none for tasks "next_time" and "remaining_time")

get_vocabulary *Utils*

Description

Utils

Usage

```
get_vocabulary(examples)
```

Arguments

examples a preprocessed dataset returned by `prepare_examples_dt()`.

max_case_length	<i>Calculate the maximum length of a case / number of activities in the longest trace in an event log</i>
-----------------	---

Description

Calculate the maximum length of a case / number of activities in the longest trace in an event log

Usage

```
max_case_length(processed_df)
```

Arguments

processed_df A processed dataset of class `ppred_examples_df` returned by `prepare_examples()`.

Value

An integer number of the maximum case length (longest trace) in an event log.

Examples

```
library(processpredictR)
library(eventdataR)

df <- prepare_examples(patients)
max_case_length(df)
```

num_outputs	<i>Calculate number of outputs (target variables)</i>
-------------	---

Description

Calculate number of outputs (target variables)

Usage

```
num_outputs(processed_df)
```

Arguments

processed_df A processed dataset of class `ppred_examples_df`.

Value

an integer number of outputs for supplying as an argument to a Transformer model, i.e. number of unique labels for a specific process monitoring task.

Examples

```
library(processpredictR)
library(eventdataR)
df <- prepare_examples(patients)
num_outputs(df)
```

plot.ppred_predictions

Plot Methods

Description

Visualize metric

Usage

```
## S3 method for class 'ppred_predictions'
plot(x, ...)
```

Arguments

x Data to plot. An object of type [ppred_predictions](#).
 ... Additional variables

Value

A ggplot object, which can be customized further, if deemed necessary.

ppred_examples_df *ppred_examples_df object*

Description

object of type [ppred_examples_df](#) is a transformed event log returned by `prepare_examples_dt()`.

ppred_model *ppred_model object*

Description

object of type [ppred_model](#) is a list returned by `processpredictR::create_model()` containing a custom keras functional (transformer) model and some other useful metrics of an event log.

ppred_predictions *ppred_predictions object*

Description

object of type `ppred_predictions` is a `data.frame` with predicted values returned by `predict.ppred_model()`.

prepare_examples *Convert a dataset of type `log` into a preprocessed format.*

Description

an event log is converted into a tibble where each row contains a cumulative sequence of activities per case. This sequence will eventually be feeded to the Transformer model's token embedding layer.

Usage

```
prepare_examples(
  log,
  task = c("outcome", "next_activity", "next_time", "remaining_time", "remaining_trace",
    "remaining_trace_s2s"),
  features = NULL,
  ...
)
```

Arguments

log	<code>log</code> : Object of class <code>log</code> or derivatives (<code>grouped_log</code> , <code>eventlog</code> , <code>activitylog</code> , etc.).
task	<code>character</code> : a process monitoring task for which to prepare an event log.
features	<code>character</code> (default <code>NULL</code>): additional features. Appends attributes (if present) <code>numeric_features</code> and/or <code>categorical_features</code> to a preprocessed event log.
...	additional arguments.

Value

a preprocessed dataset of class `ppred_examples_df`.

Examples

```
library(processpredictR)
library(eventdataR)

prepare_examples(patients, "next_activity")
```

print.ppred_model *Print methods*

Description

Print methods

Usage

```
## S3 method for class 'ppred_model'  
print(x, ...)
```

Arguments

x `ppred_model`: An object of class `ppred_model`.
... Additional Arguments.

Value

prints a Transformer model from a list returned by `create_model()`.

processpredictR *processpredictR*

Description

Means to predict process flow, such as process outcome, next activity, next time, remaining time, and remaining trace. Off-the-shelf predictive models based on the concept of Transformers are provided, as well as multiple ways to customize the models. This package is partly based on work described in Zaharah A. Bukhsh, Aaqib Saeed, & Remco M. Dijkman. (2021). "ProcessTransformer: Predictive Business Process Monitoring with Transformer Network" [arXiv:2104.00721](https://arxiv.org/abs/2104.00721).

Author(s)

Maintainer: Gert Janssenswillen <gert.janssenswillen@uhasselt.be>

Authors:

- Ivan Esin <ivan.esin@student.uhasselt>

Other contributors:

- Hasselt University [copyright holder]

split_train_test	<i>Splits the preprocessed data.frame.</i>
------------------	--

Description

Returns train- and test dataframes as a list.

Usage

```
split_train_test(processed_df, split = 0.7)
```

Arguments

processed_df A preprocessed object of type `ppred_examples_df` returned by `prepare_examples()`.
split `numeric` (default 0.7): A train-test split ratio.

Value

A `list` containing the train- and the test set objects.

Examples

```
library(processpredictR)
library(eventdataR)

df <- prepare_examples(patients, "next_activity")
split_train_test(df, split = 0.8)
```

stack_layers	<i>Stacks a keras layer on top of existing model</i>
--------------	--

Description

User friendly interface to add a keras layer on top of existing model.

Usage

```
stack_layers(object, ...)
```

Arguments

object a `list` containing a model returned by `create_model()`.
... functions for adding layers by using functional keras API. For example, `keras::layer_dense(units=32, activation="relu")`.

Value

a [list](#) containing an adapted Transformer model.

tokenize	<i>Tokenize features and target of a processed dataset of class ppred_examples_df</i>
----------	---

Description

Tokenize features and target of a processed [ppred_examples_df](#) object to fit the Transformer model.

Usage

```
tokenize(processed_df)
```

Arguments

processed_df A preprocessed object of type [ppred_examples_df](#) returned by `prepare_examples()`.

Value

A [list](#) of (sequence) tokens and additional numeric or categorical features.

vocab_size	<i>Calculate the vocabulary size, i.e. the sum of number of activities, outcome labels and padding keys</i>
------------	---

Description

Calculate the vocabulary size, i.e. the sum of number of activities, outcome labels and padding keys

Usage

```
vocab_size(processed_df)
```

Arguments

processed_df A processed dataset of class [ppred_examples_df](#) from `prepare_examples()`.

Value

an integer number of vocabulary size to define the Transformer model.

Examples

```
library(processpredictR)
library(eventdataR)
df <- prepare_examples(patients)
vocab_size(df)
```

Index

- * **visualization**
 - plot.ppred_predictions, 6
- activitylog, 7
- character, 7
- confusion_matrix, 2
- create_model, 3
- create_vocabulary, 4
- data.frame, 2, 3, 9
- eventlog, 7
- FALSE, 3
- get_vocabulary, 4
- grouped_log, 7
- keras::layer_dense(), 3
- keras::layer_embedding(), 3
- list, 3, 4, 9, 10
- log, 7
- logical, 3
- max_case_length, 5
- NULL, 7
- num_outputs, 5
- numeric, 9
- plot.ppred_predictions, 6
- ppred_examples_df, 4-6, 6, 7, 9, 10
- ppred_model, 3, 6, 6, 8
- ppred_predictions, 2, 6, 7, 7
- prepare_examples, 7
- prepare_examples(), 3
- print.ppred_model, 8
- processpredictR, 8
- processpredictR-package
 - (processpredictR), 8
- split_train_test, 9
- stack_layers, 9
- table, 2
- tokenize, 10
- TRUE, 3
- vocab_size, 10